

U4C082F

Refrigerator, Universale, Under counter, Built-in, Hinge position: Right, White, Static, F



TYPE

Product Family: Refrigerator • Installation: Built-in • Category: Under counter • Cooling type: Static • Defrost: Automatic • Hinge position: Right • Hinge type: Sliding • Reversible door: Yes • Built-in niche: 82 - 87 • EAN code: 8017709295455

AESTHETICS

Colour: White • Aesthetics: Universale • Design: Flat • Material: Metal sheet • Handle type: Fixed • Side material: Steel • Side colour: White • Door shelves profile color: White • Color of glass shelf profile: White

REFRIGERATOR COMPARTMENT FEATURES

No. of adjustable shelves: 2 • Number of fruit and vegetables drawers: 1 • Type of crisper/vegetable drawers cover: Standard • Type of adjustable shelves: Glass • Crisper Cover: Yes • Type of crisper/vegetable drawers cover: Plastic • Internal light in fridge: Yes • Type of internal light (fridge): LED

REFRIGERATOR INNER DOOR

No. of door shelves with transparent cover: 1 • Number of adjustable door shelves: 1 • No. of bottle shelves: 1

OTHER REFRIGERATOR FEATURES

Accessories: Egg tray

OTHER TECHNICAL FEATURES

Type of temperature control: Electro-mechanical • No. of compressors: 1 • Type of compressor: Standard

PERFORMANCE / ENERGY LABEL NEW 2019

Annual energy consumption: 184 kWh/a • Energy efficiency class: F • Total net volume: 106 l • Sum of the volumes of the frozen compartment(s): 16 l • Sum of the volumes of the chill compartment(s) and the unfrozen compartment(s): 90 l • Airborne acoustical noise emission class: C • Temperature Rise Time: 8.70 h • Climate class: N, ST • EEI: 125 %

ELECTRICAL CONNECTION

Electrical connection rating: 110 W • Voltage (V): 230-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 180 cm

LOGISTIC INFORMATION

Dimensions: 819x560x547 mm • Width: 560 mm • Width of the built-in niche: 600 mm • Product width with maximum doors opening: 560 mm • Height: 819 mm • Height of the built-in niche: 820 mm • Depth without handle: 547 mm • Depth of the built-in niche: 550 mm • Spacer depth: 20 mm • Net weight (kg): 31.000 kg

