

## KBT600VE

Hood, Decorative wall hood, Universale, Stainless Steel and Glass, 60 cm, B



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709289713

### AESTHETICS

Colour: Stainless Steel and Glass • Finishing: Satin • Aesthetics: Universale • Design: T flat • Material: Stainless Steel + Glass •

Type of steel: Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons

## TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1,3 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 730 m<sup>3</sup>/h • Motor power: 230 W • No. of filters: 1 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 60 kWh/a • Fluid Dynamic Efficiency (FDE): 29.1 • Lighting Efficiency (LE): 68.5 lux/W • Grease Filtering Efficiency (GFE): 81.1 % • Air flow at minimum speed (Q<sub>min</sub>): 243 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 451 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 677 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 47 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 61 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 70 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.22 W • Time increase factor (F): 1.0 • Energy Efficiency Index: 57.4 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 433 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 451 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 158 W • Nominal Power consumption of the light system (WL): 3 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 178 lux • Sound power level at highest setting (L<sub>wa</sub>): 62 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 233 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

### SPEED 1

Extraction rate IEC 61591: 243 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 48 dB(A) • Power: 142 W

### SPEED 2

Extraction rate IEC 61591: 332 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 55 dB(A) • Power: 167 W

### SPEED 3

Extraction rate IEC 61591: 451 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 190 W

### INTENSIVE SPEED

Extraction rate (IEC 61591): 677 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 227 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 520x600x450 • Width: 600 mm • Depth (mm): 450 mm • Product Height (mm): 520 mm • Net weight (kg): 12.800 kg

## ACCESSORIES INCLUDED

Tube reduction: Yes

## OPTIONAL

KITFCKBT: Accessories, HoodsKITCEKBT: Accessories, Hoods

