



KBT600XE

Hood, Decorative wall hood, Universale, Stainless steel, 60 cm, A



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709286613

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: T flat • Material: Stainless steel • Type of steel:

Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1,3 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 230 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 53 kWh/a • Fluid Dynamic Efficiency (FDE): 29.8 • Lighting Efficiency (LE): 70.4 lux/W • Grease Filtering Efficiency (GFE): 79.7 % • Air flow at minimum speed (Qmin): 261 m³/h • Air flow at maximum speed (Qmax): 473 m³/h • Air flow at boost speed (Qboost): 686 m³/h • Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 48 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 63 dB(A) • Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost): 71 dB(A) • Power consumption in stand-by mode (Ps): 0.23 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 52.0 • Measured air flow rate at best efficiency point (Qbep): 395 m³/h • Measured air pressure at best efficiency point (Pbep): 451 Pa • Measured electric power input at best efficiency point (Wbep): 159 W • Nominal Power consumption of the light system (WL): 3 W • Average illumination of the light on the cooking surface (Emiddle): 156 lux • Sound power level at highest setting (Lwa): 70 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 230 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

SPEED 1

Extraction rate IEC 61591: 260 m³/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 132 W

SPEED 2

Extraction rate IEC 61591: 358 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 152 W

SPEED 3

Extraction rate IEC 61591: 473 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 175 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 686 m³/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 222 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 520x600x450 • Width: 600 mm • Depth (mm): 450 mm • Product Height (mm): 520 mm • Net weight (kg): 12.800 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFCKBT: Accessories, HoodsKITCEKBT: Accessories, Hoods

