

## KDD60VXE-2

Hood, Fully Integrated hood, Universale, Black, 60 cm, B



### TYPE

Product family: Hood • Hood Type: Fully Integrated hood • Hood width: 60 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709223182

### AESTHETICS

Colour: Black • Finishing: Satin • Aesthetics: Universale • Design: Fully integrated • Material: Stainless steel • Type of steel: Brushed • Glass Type: Black

### PROGRAMME / FUNCTIONS

No. of speeds: 4 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Touch control • Led color: Red • Display: Digital

## TECHNICAL FEATURES

Remote motor: KITRBDD - Kit Optional • No. of lights: 1 • Light type: LED • Light Power: 7 W • Dimmer mode: Yes • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 590 m<sup>3</sup>/h • Motor power: 270 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Vent outlet: 150 mm

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): C • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 73 kWh/a • Fluid Dynamic Efficiency (FDE): 22.4 • Lighting Efficiency (LE): 29 lux/W • Grease Filtering Efficiency (GFE): 55.1 % • Air flow at minimum speed (Q<sub>min</sub>): 135 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 295 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 570 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 44 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 57 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 71 dB(A) • Power Consumption in Off mode (P<sub>o</sub>): 0.49 W • Time increase factor (F): 1.2 • Energy Efficiency Index: 69.9 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 293 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 429 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 156 W • Nominal Power consumption of the light system (WL): 7 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 200 lux • Sound power level at highest setting (L<sub>wa</sub>): 57 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

### SPEED 1

Extraction rate IEC 61591: 135 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 44 dB(A) • Power: 60 W

### SPEED 2

Extraction rate IEC 61591: 230 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 120 W

### SPEED 3

Extraction rate IEC 61591: 295 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 155 W

### SPEED 4

Extraction rate IEC 61591: 375 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 190 W

### INTENSIVE SPEED

Extraction rate (IEC 61591): 570 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 270 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 1050x537x120 • Width: 537 mm • Depth (mm): 120 mm • Product Height (mm): 1050 mm •  
Net weight (kg): 27.000 kg

## ACCESSORIES INCLUDED

Sliding door: Yes Tube reduction: Yes

## OPTIONAL

KITFCDD60: Charcoal filter, HoodsKITVENT150: Valve, HoodsRCKF2: Remote control, HoodsKITRBDD: Tube kit, Hoods

