


## KFAB75CR

Hood, Decorative wall hood, 50's Style , Cream, 75 cm, A+



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 75 cm • Extraction: Recirculation • Electronic control: Yes  
• EAN code: 8017709224875

### AESTHETICS

Colour: Cream • Finishing: Glossy • Aesthetics: 50's Style • Design: Angled • Material: Painted material • Type of steel: Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons • Led color: White

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 820 m<sup>3</sup>/h • Motor power: 280 W • No. of filters: 3 • Anti-grease filters: Stainless steel • Charcoal filters included: Yes • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 36 kWh/a • Fluid Dynamic Efficiency (FDE): 36.6 • Lighting Efficiency (LE): 68.2 lux/W • Grease Filtering Efficiency (GFE): 61.1 % • Air flow at minimum speed (Q<sub>min</sub>): 333 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 649 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 797 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 50 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 67 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 72 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.7 W • Time increase factor (F): 0.49 • Energy Efficiency Index: 39.7 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 421 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 422 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 135 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 150 lux • Sound power level at highest setting (L<sub>wa</sub>): 67 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 282 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## SPEED 1

Extraction rate IEC 61591: 333 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 198 W

## SPEED 2

Extraction rate IEC 61591: 477 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 246 W

## SPEED 3

Extraction rate IEC 61591: 649 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 286 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 797 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 294 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 644x750x616 • Width: 750 mm • Depth (mm): 616 mm • Product Height (mm): 644 mm • Net weight (kg): 26.000 kg

## ACCESSORIES INCLUDED

Sliding door: Yes Remote control: Yes

## OPTIONAL

FLTSI: Charcoal filter, HoodsKITCMNFABCR: Chimney set, Hoods

