



KICV90BL

Hood, Decorative wall hood, Universale, Black, 90 cm, A+



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709262150

AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Universale • Design: Angled • Material: Glass • Glass Type: Black

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Auto-Vent: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Touch control • Led color: Red

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Free outlet maximum capacity: 750 m³/h • Motor power: 270 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 450 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 450 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): F • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 41 kWh/a • Fluid Dynamic Efficiency (FDE): 34.8 • Lighting Efficiency (LE): 68 lux/W • Grease Filtering Efficiency (GFE): 45.1 % • Air flow at minimum speed (Q_{min}): 310 m³/h • Air flow at maximum speed (Q_{max}): 580 m³/h • Air flow at boost speed (Q_{boost}): 720 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 62 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 65 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 0.7 • Energy Efficiency Index: 40.5 • Measured air flow rate at best efficiency point (Q_{bep}): 470 m³/h • Measured air pressure at best efficiency point (P_{bep}): 470 Pa • Measured electric power input at best efficiency point (W_{bep}): 154 W • Nominal Power consumption of the light system (W_L): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 150 lux • Sound power level at highest setting (L_{wa}): 62 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 272 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

SPEED 1

Extraction rate IEC 61591: 310 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 175 W

SPEED 2

Extraction rate IEC 61591: 420 m³/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 220 W

SPEED 3

Extraction rate IEC 61591: 580 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 255 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 720 m³/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 270 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 1032x898x378 • Width: 898 mm • Depth (mm): 378 mm • Product Height (mm): 1032 mm • Net weight (kg): 13.900 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITALLFC: Charcoal filter, HoodsKITFC152: Charcoal filter, HoodsKITVENT150: Valve, Hoods

