


## KS110XE

Hood, Decorative wall hood, Universale, Stainless steel, 110 cm, B



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 110 cm • Extraction: Extraction • Electronic control: Yes  
• EAN code: 8017709201869

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: T flat • Material: Stainless steel • Type of steel:  
Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons

## TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 800 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 62 kWh/a • Fluid Dynamic Efficiency (FDE): 27.9 • Lighting Efficiency (LE): 84.1 lux/W • Grease Filtering Efficiency (GFE): 78.7 % • Air flow at minimum speed (Q<sub>min</sub>): 295 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 513 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 702 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 51 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 64 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 72 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.49 W • Time increase factor (F): 1.00 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 373 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 430 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 160 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 370 lux • Sound power level at highest setting (L<sub>wa</sub>): 64 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 278 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 295 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 51 dB(A) • Power: 207 W

### SPEED 2

Extraction rate IEC 61591: 395 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 236 W

### SPEED 3

Extraction rate IEC 61591: 513 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 250 W

### INTENSIVE SPEED

Extraction rate (IEC 61591): 702 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 314 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 1142x1100x500 • Width: 1100 mm • Depth (mm): 500 mm • Product Height (mm): 1142 mm •  
Net weight (kg): 19.900 kg

## OPTIONAL

KITALLFC: Charcoal filter, Hoods

