

KS60XE-2

Hood, Decorative wall hood, Universale, Stainless steel, 60 cm, B



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709225988

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: T flat • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Buttons

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 610 m³/h • Motor power: 200 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 54 kWh/a • Fluid Dynamic Efficiency (FDE): 24.1 • Lighting Efficiency (LE): 99.5 lux/W • Grease Filtering Efficiency (GFE): 82.7 % • Air flow at minimum speed (Q_{min}): 235 m³/h • Air flow at maximum speed (Q_{max}): 553 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 46 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 67 dB(A) • Time increase factor (F): 1.00 • Measured air flow rate at best efficiency point (Q_{bep}): 294 m³/h • Measured air pressure at best efficiency point (P_{bep}): 380 Pa • Measured electric power input at best efficiency point (W_{bep}): 129 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 219 lux • Sound power level at highest setting (L_{wa}): 67 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 202 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 235 m³/h • Noise level IEC 60704-2-13: 46 dB(A) • Power: 68 W

SPEED 2

Extraction rate IEC 61591: 323 m³/h • Noise level IEC 60704-2-13: 51 dB(A) • Power: 141 W

SPEED 3

Extraction rate IEC 61591: 553 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 191 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 600x598x470 • Width: 598 mm • Depth (mm): 470 mm • Product Height (mm): 600 mm • Net weight (kg): 14.700 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITALLFC: Charcoal filter, Hoods

