

KS905SXE2

Hood, Decorative wall hood, Linea, Stainless steel, 90 cm, A



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709253646

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Linea • Design: T flat • Material: Stainless steel • Type of steel: Brushed •

Glass Type: Stopsol

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Touch control • Led color: Ice • Display: Yes

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Dimmer mode: Yes • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 57 kWh/a • Fluid Dynamic Efficiency (FDE): 29.8 • Lighting Efficiency (LE): 83.2 lux/W • Grease Filtering Efficiency (GFE): 83.2 % • Air flow at minimum speed (Q_{min}): 320 m³/h • Air flow at maximum speed (Q_{max}): 564 m³/h • Air flow at boost speed (Q_{boost}): 767 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 50 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 65 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 73 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 52.2 • Measured air flow rate at best efficiency point (Q_{bep}): 402 m³/h • Measured air pressure at best efficiency point (P_{bep}): 451 Pa • Measured electric power input at best efficiency point (W_{bep}): 169 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 183 lux • Sound power level at highest setting (L_{wa}): 65 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 278 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 320 m³/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 196 W

SPEED 2

Extraction rate IEC 61591: 401 m³/h • Noise level IEC 60704-2-13: 61 dB(A) • Power: 232 W

SPEED 3

Extraction rate IEC 61591: 564 m³/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 270 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 767 m³/h • Noise level IEC 60704-2-13: 73 dB(A) • Power: 301 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 710x900x497 • Width: 900 mm • Depth (mm): 497 mm • Product Height (mm): 710 mm • Net weight (kg): 17.200 kg

OPTIONAL

KITALLFC: Charcoal filter, HoodsKITFC906: Charcoal filter, Hoods



