


## KSA600HXE

Hood, Decorative wall hood, Universale, Stainless steel, 60 cm, B



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709201586

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Chimney • Material: Stainless steel • Type of steel:

Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### CONTROLS

Control setting: Electronic buttons • Display: 1 a LED

## TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 2 W • Light color temperature scale (°K): 3500 °K • Free outlet maximum capacity: 650 m<sup>3</sup>/h • Motor power: 250 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 74 kWh/a • Fluid Dynamic Efficiency (FDE): 22.8 • Lighting Efficiency (LE): 29 lux/W • Grease Filtering Efficiency (GFE): 76 % • Air flow at minimum speed (Q<sub>min</sub>): 256 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 448 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 603 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 51 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 61 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 66 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.49 W • Time increase factor (F): 1.2 • Energy Efficiency Index: 69.5 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 288 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 454 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 160 W • Nominal Power consumption of the light system (WL): 5 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 145 lux • Sound power level at highest setting (L<sub>wa</sub>): 61 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 255 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

### SPEED 1

Extraction rate IEC 61591: 256 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 51 dB(A) • Power: 160 W

### SPEED 2

Extraction rate IEC 61591: 368 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 196 W

### SPEED 3

Extraction rate IEC 61591: 448 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 61 dB(A) • Power: 230 W

### INTENSIVE SPEED

Extraction rate (IEC 61591): 603 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 260 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 698x599x515 • Width: 599 mm • Depth (mm): 515 mm • Product Height (mm): 698 mm • Net weight (kg): 10.850 kg

