

KSA900HXE

Hood, Wall Decor, Universal, Stainless Steel, 90cm, B



TYPE

Family: Hood • Typology: Decorative wall • Hood width: 90cm • Filtering: Expulsion • Electronic control: Yes •

EAN Code: 8017709201593

AESTHETICS

Color: Stainless steel • Finish: Satin • Aesthetics: Universal • Design: Trapezium • Material: Stainless steel • Stainless steel type: Satin

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

COMMANDS

Control adjustment: Electronic keys • Display: 1aLED

TECHNICAL FEATURES

N° dilution: 2 • TipodiLight: LED • Potenza luce: 2W • Temperatura di colore della luce (°K): 3500°K • Capacity

free mode suction (P0): 650m³ / h • Motor power: 250W • No. of filters: 3 • Grease filter: Aluminum • Indicator

change filtri: Yes • Minima installazione da piano cottura a gas distance: 650mm • Imbocco motore diameter: 150mm • Distance

minimum installation of electric cooktop: 500mm • Non-return valve: Yes

PERFORMANCE / ENERGY LABEL

Classediefficienzaenergetica(EEC):B•Classediefficienzafluidodinamica(FDEC):C•Classediefficienzafiltraggiograssi (GFEC):C•Classification Regulation(LEC):A•Efficiency Regulation(AEC):74kWh/a•Efficiency dynamic (FDE): 22.8 • Lighting efficiency (LE): 76.1lux / W • Grease filtering efficiency (GFE): 76% • Airflow to velocitàminima(Qmin):256m³/h•Portatad'ariaallavelocitàmassima(Qmax):448m³/h•Portatad'ariaallavelocitàintensiva (Qboost):603m³/h•Emissioneponderatadipotenzaacusticaallavelocitàminima(SPEmin):51dB(A)•Emissioneponderatadi acoustic power at maximum speed (SPEmax): 61dB (A) • Weighted emission of acoustic power at intensive speed (SPEboost):66dB(A)•Assorbimentoistand-by(Ps):0.49W•Fattoreidamentodeltempo(F):1.2•Indicediefficienza energy: 69.5 • Measured air flow in conditions of maximum efficiency (Qbep): 288m³ / h • Measured air pressure in the condition of maximum efficiency (Pbep): 454Pa • Electric power absorbed in the condition of maximum efficiency (Wbep): 159W Potenzanominaledeilsistemadiilluminazione (WL): 5W Illuminazionemediadel sistemadiilluminazione on the top floor (Emiddle): 381lux • Highest sound level (Lwa): 61dB (A)

ELECTRICAL CONNECTION

Electrical connection nominal data: 255W • Voltage: 220-240V • Frequency: 50-60Hz • Cable length feed: 1500mm

OPTIONALS NON INCLUSI

SPEED 1

Suction capacity (IEC61591): 256m³ / h • Noise level (IEC60704-2-13): 51dB (A) • Power: 160W

SPEED 2

Suction capacity (IEC61591): 368m³ / h • Noise level (IEC60704-2-13): 57dB (A) • Power: 196W

SPEED 3

Suction capacity (IEC61591): 480m³ / h • Noise level (IEC60704-2-13): 61dB (A) • Power: 230W

SPEED 4

INTENSIVE SPEED

Suction capacity (IEC61591): 603m³ / h • Noise level (IEC60704-2-13): 66dB (A) • Power: 260W

LOGISTICS INFORMATION

Dimensionidelprodotto(mm):698x899x515•Larghezza:899mm•Profonditàdelprodotto(mm):515mm•Altezzadel

Product (mm): 698mm • Weight (kg): 12.600kg

