

## KSDD90VN-2

Hood, Fully Integrated hood, Dolce Stil Novo, Black, 90 cm, A



### TYPE

Product family: Hood • Hood Type: Fully Integrated hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709239336

### AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Dolce Stil Novo • Design: Fully integrated • Material: Stainless Steel + Glass • Type of steel: Brushed • Glass Type: Black

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Remote Control

### TECHNICAL FEATURES

Remote motor: Included • No. of lights: 1 • Light type: LED • Light Power: 6 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 800 m<sup>3</sup>/h • Motor power: 285 W • No. of filters: 2 • Anti-grease filters: stainless steel 7 layer • Vent outlet: 150 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): G • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC<sub>hood</sub>): 60 kWh/a • Fluid Dynamic Efficiency (FDE): 29.5 • Lighting Efficiency (LE): 15.0 lux/W • Grease Filtering Efficiency (GFE): 38.9 % • Air flow at minimum speed (Q<sub>min</sub>): 213 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 448 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 724 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 40 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 57 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 65 dB(A) • Time increase factor (F): 1.00 • Energy Efficiency Index: 53.1 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 349 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 464 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 147 W • Nominal Power consumption of the light system (WL): 6 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 253 lux • Sound power level at highest setting (L<sub>wa</sub>): 57 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 292 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## SPEED 1

Extraction rate IEC 61591: 230 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 42 dB(A) • Power: 80 W

## SPEED 2

Extraction rate IEC 61591: 322 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 141 W

## SPEED 3

Extraction rate IEC 61591: 500 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 203 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 730 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 273 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 780x900x120 • Width: 900 mm • Depth (mm): 120 mm • Product Height (mm): 780 mm • Net weight (kg): 60.000 kg

## ACCESSORIES INCLUDED

Sliding door: Yes Remote control: Yes





