

## KSED65XE

Hood, Decorative wall hood, Universale, Stainless steel, 60 cm, B



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709206079

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Chimney • Material: Stainless steel • Type of steel: Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3

### CONTROLS

Control setting: Slider

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 600 m<sup>3</sup>/h • Motor power: 200 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class ( EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 60 kWh/a • Fluid Dynamic Efficiency (FDE): 26 • Lighting Efficiency (LE): 100.2 lux/W • Grease Filtering Efficiency (GFE): 74.4 % • Air flow at minimum speed (Q<sub>min</sub>): 351 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 635 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 53 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 67 dB(A) • Time increase factor (F): 1.1 • Energy Efficiency Index: 62.2 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 355 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 385 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 146 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 221 lux • Sound power level at highest setting (L<sub>wa</sub>): 67 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 202 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## SPEED 1

Extraction rate IEC 61591: 351 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 53 dB(A) • Power: 140 W

## SPEED 2

Extraction rate IEC 61591: 420 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 157 W

## SPEED 3

Extraction rate IEC 61591: 635 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 191 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 652x600x514 • Width: 600 mm • Depth (mm): 514 mm • Product Height (mm): 652 mm • Net weight (kg): 11.200 kg

## OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods



