

## KSEG58PXE

Hood, Integrated hood, Universale, Stainless steel, 54 cm, A



### TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 54 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709224912

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Fully integrated • Material: Stainless steel • Type of steel: Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons • Led color: White

## TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 673 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 46 kWh/a • Fluid Dynamic Efficiency (FDE): 31.7 • Lighting Efficiency (LE): 111.8 lux/W • Grease Filtering Efficiency (GFE): 56.9 % • Air flow at minimum speed (Q<sub>min</sub>): 261 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 606 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 683 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 46 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 65 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 68 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 50.7 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 329 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 466 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 134 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 246 lux • Sound power level at highest setting (L<sub>wa</sub>): 65 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

### SPEED 1

Extraction rate IEC 61591: 261 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 46 dB(A) • Power: 199 W

### SPEED 2

Extraction rate IEC 61591: 436 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 219 W

### SPEED 3

Extraction rate IEC 61591: 606 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 233 W

### INTENSIVE SPEED

Extraction rate (IEC 61591): 683 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 68 dB(A) • Power: 228 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 335x540x300 • Width: 540 mm • Depth (mm): 300 mm • Product Height (mm): 335 mm • Net weight (kg): 10.000 kg

