

## KSET61E2

Hood, Integrated (semi) hood, Universale, Silver, 60 cm, D



### TYPE

Product family: Hood • Hood Type: Integrated (semi) hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709274788

### AESTHETICS

Colour: Silver • Aesthetics: Universale • Design: Telescopic • Material: Painted material

### PROGRAMME / FUNCTIONS

No. of speeds: 3

### CONTROLS

Control setting: Slider

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 4 W • Free outlet maximum capacity: 315 m<sup>3</sup>/h • Motor power: 125 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 120 mm • Minimum distance from ELECTRIC hob: 450 mm

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC<sub>hood</sub>): 70 kWh/a • Fluid Dynamic Efficiency (FDE): 8.1 • Lighting Efficiency (LE): 13 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q<sub>min</sub>): 180 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 310 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 57 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 67 dB(A) • Time increase factor (F): 1.7 • Energy Efficiency Index: 91.4 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 164 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 183 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 103 W • Nominal Power consumption of the light system (WL): 8 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 100 lux • Sound power level at highest setting (L<sub>wa</sub>): 67 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 133 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1000 mm

## SPEED 1

Extraction rate IEC 61591: 180 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 85 W

## SPEED 2

Extraction rate IEC 61591: 220 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 100 W

## SPEED 3

Extraction rate IEC 61591: 310 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 125 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 175x598x310 • Width: 598 mm • Depth (mm): 310 mm • Product Height (mm): 175 mm • Net weight (kg): 7.600 kg

## OPTIONAL

KITFC6191: Charcoal filter, Hoods

