

KSET62E

Hood, Integrated (semi) hood, Universale, Silver, 60 cm, D









TYPE

Product family: Hood • Hood Type: Integrated (semi) hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709233044

AESTHETICS

Colour: Silver • Aesthetics: Universale • Design: Telescopic • Material: Painted material

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Buttons

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 3 W • Light color temperature scale (°K): 2700 °K • Free outlet maximum capacity: 304 m³/h • Motor power: 115 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 120 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEChood): 62 kWh/a • Fluid Dynamic Efficiency (FDE): 10.3 • Lighting Efficiency (LE): 13 lux/W • Grease Filtering Efficiency (GFE): 66 % • Air flow at minumum speed (Qmin): 125 m³/h • Air flow at maximum speed (Qmax): 304 m³/h • Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin): 46 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 62 dB(A) • Time increase factor (F): 1.6 • Measured air flow rate at best efficiency point (Qbep): 198 m³/h • Measured air pressure at best efficiency point (Pbep): 187 Pa • Measured electric power input at best efficiency point (Wbep): 99 W • Nominal Power consumption of the light system (WL): 6 W • Average illumination of the light on the cooking surface (Emiddle): 78 lux • Sound power level at highest setting (Lwa): 62 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 121 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 125 m³/h • Noise level IEC 60704-2-13: 46 dB(A) • Power: 43 W

SPEED 2

Extraction rate IEC 61591: 160 m³/h • Noise level IEC 60704-2-13: 48 dB(A) • Power: 65 W

SPEED 3

Extraction rate IEC 61591: 304 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 115 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 180x598x280 ◆ Width: 598 mm ◆ Depth (mm): 280 mm ◆ Product Height (mm): 180 mm ◆ Net weight (kg): 6.000 kg

OPTIONAL

KITFC62: Charcoal filter, Hoods







