


KSET66E

Hood, Integrated (semi) hood, Universale, Stainless steel, 60 cm, C



TYPE

Product family: Hood • Hood Type: Integrated (semi) hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709203436

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Telescopic • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Free outlet maximum capacity: 620 m³/h • Motor power: 140 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): C • Fluid Dynamic Efficiency class (FDEC): D • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 78 kWh/a • Fluid Dynamic Efficiency (FDE): 14.4 • Lighting Efficiency (LE): 59 lux/W • Grease Filtering Efficiency (GFE): 76 % • Air flow at minimum speed (Q_{min}): 295 m³/h • Air flow at maximum speed (Q_{max}): 580 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 68 dB(A) • Time increase factor (F): 1.5 • Energy Efficiency Index: 83.5 • Measured air flow rate at best efficiency point (Q_{bep}): 322 m³/h • Measured air pressure at best efficiency point (P_{bep}): 224 Pa • Measured electric power input at best efficiency point (W_{bep}): 139 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 130 lux • Sound power level at highest setting (L_{wa}): 68 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 142 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

SPEED 1

Extraction rate IEC 61591: 295 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 1 W

SPEED 2

Extraction rate IEC 61591: 435 m³/h • Noise level IEC 60704-2-13: 61 dB(A) • Power: 1 W

SPEED 3

Extraction rate IEC 61591: 580 m³/h • Noise level IEC 60704-2-13: 68 dB(A) • Power: 1 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 260x598x280 • Width: 598 mm • Depth (mm): 280 mm • Product Height (mm): 260 mm • Net weight (kg): 9.000 kg

OPTIONAL

KITFC152: Charcoal filter, Hoods

