


KSG52HE

Hood, Integrated hood, Universale, Silver, 54 cm, D



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 54 cm • Extraction: Extraction • EAN code: 8017709275143

AESTHETICS

Colour: Silver • Aesthetics: Universale • Design: Fully integrated • Material: Painted material

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 3 W • Light color temperature scale (°K): 2700 °K • Free outlet maximum capacity: 406 m³/h • Motor power: 140 W • No. of filters: 1 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 120 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC_{hood}): 71 kWh/a • Fluid Dynamic Efficiency (FDE): 11 • Lighting Efficiency (LE): 12.1 lux/W • Grease Filtering Efficiency (GFE): 66 % • Air flow at minimum speed (Q_{min}): 290 m³/h • Air flow at maximum speed (Q_{max}): 368 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 62 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 67 dB(A) • Time increase factor (F): 1.6 • Energy Efficiency Index: 87.3 • Measured air flow rate at best efficiency point (Q_{bep}): 206 m³/h • Measured air pressure at best efficiency point (P_{bep}): 218 Pa • Measured electric power input at best efficiency point (W_{bep}): 113 W • Nominal Power consumption of the light system (WL): 6 W • Average illumination of the light on the cooking surface (E_{middle}): 73 lux • Sound power level at highest setting (L_{wa}): 67 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 146 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz

SPEED 1

Extraction rate IEC 61591: 288 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 104 W

SPEED 2

Extraction rate IEC 61591: 340 m³/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 122 W

SPEED 3

Extraction rate IEC 61591: 368 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 140 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 208x534x300 • Width: 534 mm • Depth (mm): 300 mm • Product Height (mm): 208 mm • Net weight (kg): 4.300 kg

OPTIONAL

KITFC62: Charcoal filter, Hoods

