



KV26P

Hood, Decorative wall hood, Coloniale, Cream, 60 cm, A



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Recirculation • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709303334

AESTHETICS

Colour: Cream • Finishing: Glass • Aesthetics: Coloniale • Design: Angled • Material: Glass • Glass Type: Black

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Touch control back-lighted White • Led color: White

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1,1 W • Dimmer mode: Yes • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 670 m³/h • Motor power: 230 W • No. of filters: 2 • Anti-grease filters: Aluminium • Charcoal filters included: Yes • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 450 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 49 kWh/a • Fluid Dynamic Efficiency (FDE): 31.5 • Lighting Efficiency (LE): 118.6 lux/W • Grease Filtering Efficiency (GFE): 77.0 % • Air flow at minimum speed (Qmin): 242 m³/h • Air flow at maximum speed (Qmax): 420 m³/h • Air flow at boost speed (Qboost): 666 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 44 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 58 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 67 dB(A) • Power consumption in stand-by mode (Ps): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 51.1 • Measured air flow rate at best efficiency point (Qbep): 363 m³/h • Measured air pressure at best efficiency point (Pbep): 453 Pa • Measured electric power input at best efficiency point (Wbep): 145 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (Emiddle): 261 lux • Sound power level at highest setting (Lwa): 58 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 232 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

SPEED 1

Extraction rate IEC 61591: 242 m³/h • Noise level IEC 60704-2-13: 44 dB(A) • Power: 137 W

SPEED 2

Extraction rate IEC 61591: 326 m³/h • Noise level IEC 60704-2-13: 51 dB(A) • Power: 157 W

SPEED 3

Extraction rate IEC 61591: 420 m³/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 183 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 666 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 224 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 459x595x439 • Width: 595 mm • Depth (mm): 439 mm • Product Height (mm): 459 mm • Net weight (kg): 14.180 kg

OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

