


KV90XE

Hood, Decorative wall hood, Universale, Stainless steel, 90 cm, B



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709206116

AESTHETICS

Colour: Stainless steel • Finishing: Glass • Aesthetics: Universale • Design: Curved • Material: Glass • Type of steel: Brushed •

Glass Type: Clear

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led color: White

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 780 m³/h • Motor power: 278 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes •

Vent outlet: 150 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 65 kWh/a • Fluid Dynamic Efficiency (FDE): 27.5 • Lighting Efficiency (LE): 118.6 lux/W • Grease Filtering Efficiency (GFE): 80.2 % • Air flow at minimum speed (Q_{min}): 313 m³/h • Air flow at maximum speed (Q_{max}): 535 m³/h • Air flow at boost speed (Q_{boost}): 764 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 64 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 71 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 1.00 • Measured air flow rate at best efficiency point (Q_{bep}): 406 m³/h • Measured air pressure at best efficiency point (P_{bep}): 426 Pa • Measured electric power input at best efficiency point (W_{bep}): 174 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 261 lux • Sound power level at highest setting (L_{wa}): 64 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 278 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 313 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 202 W

SPEED 2

Extraction rate IEC 61591: 419 m³/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 238 W

SPEED 3

Extraction rate IEC 61591: 535 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 261 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 764 m³/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 278 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 850x898x490 • Width: 898 mm • Depth (mm): 490 mm • Product Height (mm): 850 mm • Net weight (kg): 17.000 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITALLFC: Charcoal filter, HoodsKITFC161: Charcoal filter, Hoods

